

1 Apache::Constants - Constants defined in apache header files

1.1 Synopsis

```
use Apache::Constants;
use Apache::Constants ':common';
use Apache::Constants ':response';
```

1.2 Description

Server constants used by apache modules are defined in **httpd.h** and other header files, this module gives Perl access to those constants.

1.3 Export Tags

- **common**

This tag imports the most commonly used constants.

```
OK
DECLINED
DONE
NOT_FOUND
FORBIDDEN
AUTH_REQUIRED
SERVER_ERROR
```

- **response**

This tag imports the **common** response codes, plus these response codes:

```
DOCUMENT_FOLLOWS
MOVED
REDIRECT
USE_LOCAL_COPY
BAD_REQUEST
BAD_GATEWAY
RESPONSE_CODES
NOT_IMPLEMENTED
CONTINUE
NOT_AUTHORITATIVE
```

CONTINUE and **NOT_AUTHORITATIVE** are aliases for **DECLINED**.

- **methods**

This are the method numbers, commonly used with the Apache **method_number** method.

```
METHODS
M_CONNECT
M_DELETE
M_GET
M_INVALID
```

```
M_OPTIONS
M_POST
M_PUT
M_TRACE
M_PATCH
M_PROPFIND
M_PROPPATCH
M_MKCOL
M_COPY
M_MOVE
M_LOCK
M_UNLOCK
```

- **options**

These constants are most commonly used with the Apache **allow_options** method:

```
OPT_NONE
OPT_INDEXES
OPT_INCLUDES
OPT_SYM_LINKS
OPT_EXECCGI
OPT_UNSET
OPT_INCNOEXEC
OPT_SYM_OWNER
OPT_MULTI
OPT_ALL
```

- **satisfy**

These constants are most commonly used with the Apache **satisfies** method:

```
SATISFY_ALL
SATISFY_ANY
SATISFY_NOSPEC
```

- **remotehost**

These constants are most commonly used with the Apache **get_remote_host** method:

```
REMOTE_HOST
REMOTE_NAME
REMOTE_NOLOOKUP
REMOTE_DOUBLE_REV
```

- **http**

This is the full set of HTTP response codes: (NOTE: not all implemented here)

```
HTTP_OK
HTTP_MOVED_TEMPORARILY
HTTP_MOVED_PERMANENTLY
HTTP_METHOD_NOT_ALLOWED
HTTP_NOT_MODIFIED
HTTP_UNAUTHORIZED
HTTP_FORBIDDEN
```

```
HTTP_NOT_FOUND
HTTP_BAD_REQUEST
HTTP_INTERNAL_SERVER_ERROR
HTTP_NOT_ACCEPTABLE
HTTP_NO_CONTENT
HTTP_PRECONDITION_FAILED
HTTP_SERVICE_UNAVAILABLE
HTTP_VARIANT_ALSO_VARIES
```

- **server**

These are constants related to server version:

```
MODULE_MAGIC_NUMBER
SERVER_VERSION
SERVER_BUILT
```

- **config**

These are constants related to configuration directives:

```
DECLINE_CMD
```

- **types**

These are constants related to internal request types:

```
DIR_MAGIC_TYPE
```

- **override**

These constants are used to control and test the context of configuration directives.

```
OR_NONE
OR_LIMIT
OR_OPTIONS
OR_FILEINFO
OR_AUTHCFG
OR_INDEXES
OR_UNSET
OR_ALL
ACCESS_CONF
RSRC_CONF
```

- **args_how**

```
RAW_ARGS
TAKE1
TAKE2
TAKE12
TAKE3
TAKE23
TAKE123
ITERATE
ITERATE2
FLAG
NO_ARGS
```

1.4 Warnings

You should be aware of the issues relating to using constant subroutines in Perl. For example, look at this example:

```
$r->custom_response(FORBIDDEN => "File size exceeds quota.");
```

This will not set a custom response for FORBIDDEN, but for the string "FORBIDDEN", which clearly isn't what is expected. You'll get an error like this:

```
[Tue Apr 23 19:46:14 2002] null: Argument "FORBIDDEN" isn't numeric in subroutine entry at ...
```

Therefore, you can avoid this by not using the hash notation for things that don't require it.

```
$r->custom_response(FORBIDDEN, "File size exceeds quota.");
```

Another important note is that you should be using the correct constants defined here, and not direct HTTP codes. For example:

```
sub handler {
    return 200;
}
```

Is not correct. The correct use is:

```
use Apache::Constants qw(OK);

sub handler {
    return OK;
}
```

Also remember that OK != HTTP_OK.

1.5 Maintainers

Maintainer is the person(s) you should contact with updates, corrections and patches.

- **The documentation mailing list**

1.6 Authors

- **Doug MacEachern**
- **Gisle Aas**
- **h2xs**

Only the major authors are listed above. For contributors see the Changes file.

Table of Contents:

1	Apache::Constants - Constants defined in apache header files	1
1.1	Synopsis	2
1.2	Description	2
1.3	Export Tags	2
1.4	Warnings	5
1.5	Maintainers	5
1.6	Authors	6