

1 Apache::Symdump - Symbol table snapshots

1.1 Synopsis

```
PerlLogHandler Apache::Symdump
```

1.2 Description

Apache::Symdump will record snapshots of the Perl symbol table for you to look at later.

It records them in `ServerRoot/logs/symdump.$$.$n`. Where `$$` is the process id and `$n` is incremented each time the handler is run. The `diff` utility can be used to compare snapshots and get an idea of what might be making a process grow. Normally, new symbols come from modules or scripts that were not preloaded, the Perl method cache, etc.

```
% diff -u symdump.$$0 symdump.$$1
```

1.3 Caveats

Apache::Symdump does not cleanup up its snapshot files, do so simply by:

```
% rm logs/symdump.* logs/incdump.*
```

1.4 See Also

Devel::Symdump, Apache::Leak

1.5 Maintainers

Maintainer is the person(s) you should contact with updates, corrections and patches.

- **The documentation mailing list**

1.6 Authors

- **Doug MacEachern**

Only the major authors are listed above. For contributors see the Changes file.

Table of Contents:

1	Apache::Symdump - Symbol table snapshots	1
1.1	Synopsis	2
1.2	Description	2
1.3	Caveats	2
1.4	See Also	2
1.5	Maintainers	2
1.6	Authors	2